

SECTION A - A

- 1. STORMWATER TREATMENT SYSTEM (SWTS) SHALL HAVE: PEAK TREATMENT CAPACITY: 708L/S SEDIMENT STORAGE: 5.43M3 SEDIMENT CHAMBER DIA: 3658MM
- 2. SWTS SHALL BE CONTAINED IN ONE RECTANGULAR STRUCTURE
- 3. SWTS REMOVAL EFFICIENCY SHALL BE DOCUMENTED BASED ON PARTICLE SIZE
- 4. SWTS SHALL RETAIN FLOATABLES AND TRAPPED SEDIMENT UP TO AND INCLUDING PEAK TREATMENT CAPACITY
- 5. SWTS INVERTS IN AND OUT ARE TYPICALLY AT THE SAME ELEVATION
- 6. SWTS SHALL NOT BE COMPROMISED BY EFFECTS OF DOWNSTREAM TAILWATER
- 7. SWTS SHALL HAVE NO INTERNAL COMPONENTS THAT OBSTRUCT MAINTENANCE
- 8. INLET PIPE MUST BE PERPENDICULAR TO THE STRUCTURE
- 9. PIPE ORIENTATION MAY VARY; SEE SITE PLAN FOR SIZE AND LOCATION
- 10. PURCHASER SHALL NOT BE RESPONSIBLE FOR ASSEMBLY OF UNIT
- 11. MANHOLE FRAMES AND PERFORATED COVERS SUPPLIED WITH SYSTEM, NOT **INSTALLED**
- 12. PURCHASER TO PREPARE EXCAVATION AND PROVIDE CRANE FOR
- 13. VORTECHS SYSTEMS BY STORMWATER360:
- AUCKLAND (09) 476 5586 BRISBANE (07) 3272 1872 SYDNEY (02) 9525 5833 14. VORTECHS SYSTEM HAS BEEN DESIGNED IN ACCORDANCE WITH RELEVANT AUSTRALIAN ANS NEW ZEALAND STANDARDS FOR 0-2m FILL AND T44 (HNHO-72) LIVE LOADINGS ONLY. FOR OTHER LOADING CONDITIONS PLEASE CONTACT

PROPRIETARY INFORMATION - NOT TO BE USED FOR CONSTRUCTION PURPOSES

This CADD file is for the purpose of specifying stormwater treatment equipment to be furnished by STORMWATER360 and may only be transferred to other documents exactly as provided by STORMWATER360. Title block information, excluding the STORMWATER360 logo and the Vortechs Stormwater Treatment System designation and patent number, may be deleted if necessary. Revisions to any part of this CADD file without prior coordination with STORMWATER360 shall be considered unauthorized use of proprietary information.

www.stormwater360.co.nz www.stormwater360.com.au



STORMWATER360

STORMWATER TREATMENT SYSTEM **VORTECHS MODEL 16000 METRIC** STANDARD DETAIL

DRAWING

DRN: R.P.

CHK: M.W

SCALE N.T.S.

FILE NAME:

STD16KM